



552978

(43) International Publication Date
20 January 2005 (20.01.2005)

PCT

(10) International Publication Number
WO 2005/006299 A1

(51) International Patent Classification⁷: G09G 3/34, 3/36

(21) International Application Number:
PCT/JP2004/010081

(22) International Filing Date: 8 July 2004 (08.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-194589 9 July 2003 (09.07.2003) JP

(71) Applicant (for all designated States except US): CANON
KABUSHIKI KAISHA [JP/JP]; 30-2, Shimomaru
3-chome, Ohta-ku, Tokyo 146-8501 (JP).

(72) Inventor; and

(75) Inventor/Applicant (for US only): MATSUDA, Yojiro
[JP/JP]; 228-2-A201, Manpukuji, Asao-ku, Kawasaki-shi,
Kanagawa 215-0004 (JP).



(74) Agent: YAMADA, Ryuichi; Toko International Patent Of-
fice, Hasegawa Bldg. 4F, 7-7, Toranomom 3-chome, Mi-
nato-ku, Tokyo 105-0001 (JP).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: DISPLAY APPARATUS



(57) Abstract: In a display apparatus using charged electrophoretic particles, being controlled by an electric field at the pixels, in some cases the charged particles fail to display a desired gradation level even when a voltage is applied to the pixel with the intention of providing the desired gradation level. In such cases, correction values for all the gradation levels are obtained in advance by experiment, and then a corrected voltage is applied to the pixel, whereby it is possible to provide a desired gradation by compensating an influence of an electric field at adjacent pixels.



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*